

IVX S-Class Administrator worksheets

These Administrator worksheets are for use with **any** IVX S-Class system.

Function 1: System parameters

F13 — Administrator password

Range: 2–8 digits. Default: 456.

F14 — Set time/date

F141: Set time and date

F142: Automatic time settings

Synchronize with Caller ID

Default: Enabled.

Adjust for Daylight Savings Time

Default: Enabled.

F17 — System speed-dial

(Use the worksheet on the following page.)

F17 — System speed dial

Loc.	Name	Number
600		
601		
602		
603		
604		
605		
606		
607		
608		
609		
610		
611		
612		
613		
614		
615		
616		
617		
618		
619		
620		
621		
622		
623		
624		
625		

(Use a blank sheet for additional speed dial numbers 626–699.)

Function 3: Extension programming

F32 – Extension feature authorization

	Ext.	Name	Rec.	Toll allow	Sys. spd. dl.	Ext. fwd.	Fwd. toll	Trunk-trunk
	Default		Y*	Y	Y	N	N	N
1								
2								
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								
35								
36								
37								
38								
39								
40								

Make copies for additional extensions.

* Does not apply to 12-Key Feature Phones or analog extensions.

F55 — Message notification

F551: Station delivery options

Mailbox		Number	Delay	Attempts	Interval	Quiet on	Quiet off
Range	Phone	Up to 24 digits	0-500	0-99	10-1,440	None	None
Range	Pager	Up to 24 digits	0-500	0-99	10-1,440		
Default	Phone	None	0	3	30	None	None
Default	Pager	None	0	3	30		

1	Phone						
	Pager						
2	Phone						
	Pager						
3	Phone						
	Pager						
4	Phone						
	Pager						
5	Phone						
	Pager						
6	Phone						
	Pager						
7	Phone						
	Pager						
8	Phone						
	Pager						
9	Phone						
	Pager						
10	Phone						
	Pager						
11	Phone						
	Pager						
12	Phone						
	Pager						

Make copies for additional mailboxes.

F552: Delivery/paging parameters

CO line access

Range: 9, 8, 7. Default: 9.

Maximum lines

Range: 1-19. Default: 1.

Pager dialing pause

Range: 0-20. Default: 6.

F56 — Cascade paging mailboxes

Attempts — Range: 0–99. Default: 0.

Paging interval — Range: 0 (page only once)–1,440. Default: 0.

Mailbox	Option 1			Option 2		
	1st number	Attempts	2nd number	Attempts	3rd number	Paging interval
520						
521						
522						
523						
524						
525						
526						
527						
528						
529						

Function 6: Recordings

F61 — Re-recordable prompts

Prompt	Type	Default	Re-recorded
530	Busy prompt	<input type="checkbox"/>	<input type="checkbox"/>
531	No answer	<input type="checkbox"/>	<input type="checkbox"/>
532	Hold	<input type="checkbox"/>	<input type="checkbox"/>
534	Q/Z	<input type="checkbox"/>	<input type="checkbox"/>
535	No names matched	<input type="checkbox"/>	<input type="checkbox"/>
537	End of recording	<input type="checkbox"/>	<input type="checkbox"/>
540	Holiday greeting	<input type="checkbox"/>	<input type="checkbox"/>

F62 — Record directory names

(Use the worksheet on the following page.)

Prompt for first name/last name

Options: "Select by first name" (default); "Select by last name."

F63 — Message-on hold-programming

F631: MOH source

Range: 590–598. Default: 592

F632: MOH recording

(See *Installation Manual* for instructions.)

F633: MOH volume

Range: 1–12. Default: 6

